

**(12) DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION**

(13) A1

(86) Date de dépôt PCT/PCT Filing Date: 2001/04/20
(87) Date publication PCT/PCT Publication Date: 2001/11/01
(85) Entrée phase nationale/National Entry: 2002/10/17
(88) N° demande PCT/PCT Application No.: CA 2001/000534
(87) N° publication PCT/PCT Publication No.: 2001/081065
(30) Priorité/Priority: 2000/04/20 (60/198,691) US


(51) Cl.int⁷/Int.Cl.⁷ B29C 45/16

(71) **Demandeurs/Applicants:**
DECOMA EXTERIOR TRIM INC., CA;
OMNOVA SOLUTIONS INC., US

(72) Inventors/Inventors:
MORI, STEVEN J., CA;
HOUTARI, KEIJO J., US;
STRAUS, ELLIOTT J., US
BRETT, MICHAEL, CA

(74) Agent: IMAI, JEFFREY T.

(54) Titre : PROCEDE DE MOULAGE DE PANNEAU
(54) Title: METHOD OF MOLDING A PANEL



(57) Abrégé/Abstract

(57) Abrégé/Abstract:
A method of manufacturing a panel utilizes a first mold half (12) having a peripherally extending rib (24) and a second mold half (14). The first mold half (12) is moved relative to the second mold half (14) to define a first mold cavity with the rib extending into the first mold cavity. A first molten material (20) is injected into the first mold cavity and allowed to solidify to thereby form a notch (26) within the first solidified material (20) corresponding to the shape of the rib (24). A second mold cavity is formed which has a flow path between the first solidified material (20) and the first mold half (12) comprising a series of sharp turns which present a barrier to material flow. A second material (30) is injected into the second mold cavity and allowed to cure on the first solidified material.